



Wireless Telephone Configuration

Info System SIP Provisioning Regional Phone **Ext 1** User

[User Login](#)

General

Line Enable: yes

Share Line Appearance

Share Ext: private

Shared User ID:

Subscription Expires: 3600

NAT Settings

NAT Mapping Enable: no

NAT Keep Alive Enable: no

NAT Keep Alive Msg: \$NOTIFY

NAT Keep Alive Dest: \$PROXY

Network Settings

SIP TOS/DiffServ Value: 0x68

SIP CoS Value: 3

RTP TOS/DiffServ Value: 0xb8

RTP CoS Value: 6

Network Jitter Level: high

Jitter Buffer Adjustment: up and down

SIP Settings

SIP Transport: UDP

SIP Port: 5060

SIP 100REL Enable: no

EXT SIP Port:

Auth Resync-Reboot: yes

SIP Proxy-Require:

SIP Remote-Party-ID: yes

Referor Bye Delay: 4

Refer-To Target Contact: yes

Referee Bye Delay: 0

SIP Debug Option: none

Refer Target Bye Delay: 0

Sticky 183: no

Set G729 annexb: none

Call Feature Settings

Blind Attn-Xfer Enable: no

MOH Server:

Message Waiting: no

Auth Page: no

Auth Page Realm:

Conference Bridge URL:

Auth Page Password:

Mailbox ID:

Voice Mail Server:

State Agent:

CFWD Notify Serv: no

CFWD Notifier:

Proxy and Registration

Proxy: 172.24.2.5

Use Outbound Proxy: no

Outbound Proxy:

Use OB Proxy In Dialog: yes

Register: yes

Make Call Without Reg: no

Register Expires: 3600

Ans Call Without Reg: no

Use DNS SRV: no

DNS SRV Auto Prefix: no

Proxy Fallback Intvl: 3600

Proxy Redundancy Method: Normal

Subscriber Information

Display Name: House

User ID: ext105

Password: *****

Use Auth ID: yes

Auth ID: ext105

Mini Certificate:

SRTP Private Key:

Audio Configuration

Preferred Codec: G711u

Use Pref Codec Only: no

G729a Enable: yes

G726-32 Enable: yes

Release Unused Codec:	yes <input type="checkbox"/>	DTMF Process AVT:	yes <input type="checkbox"/>
Silence Supp Enable:	no <input type="checkbox"/>	DTMF Tx Method:	Auto <input type="checkbox"/>
Dial Plan			
Dial Plan:	(*xx [3469]11 0 00 [2-9]xxxxxx 1xxx[2-9]xxxxxxS0 xxxxxxxxxxxxx.)		
Enable IP Dialing:	yes <input type="checkbox"/>		

Undo All Changes

Submit All Changes

Copyright © 2008 Cisco Systems Inc. All Rights Reserved.