



Linksys Phone Adapter Configuration

Router

Voice

[Info](#) | [System](#) | **[SIP](#)** | [Provisioning](#) | [Regional](#) | [Line 1](#) | [PSTN Line](#) | [User 1](#) | [PSTN User](#) |
 [User Login](#) | [basic](#) | [advanced](#)

SIP Parameters

Max Forward:	70	Max Redirection:	5
Max Auth:	2	SIP User Agent Name:	\$VERSION
SIP Server Name:	\$VERSION	SIP Reg User Agent Name:	
SIP Accept Language:		DTMF Relay MIME Type:	application/dtmf-relay
Hook Flash MIME Type:	application/hook-flash	Remove Last Reg:	no
Use Compact Header:	no	Escape Display Name:	no
RFC 2543 Call Hold:	yes	Mark All AVT Packets:	yes
SIP TCP Port Min:	5060	SIP TCP Port Max:	5080

SIP Timer Values (sec)

SIP T1:	.5	SIP T2:	4
SIP T4:	5	SIP Timer B:	32
SIP Timer F:	32	SIP Timer H:	32
SIP Timer D:	32	SIP Timer J:	32
INVITE Expires:	240	ReINVITE Expires:	30
Reg Min Expires:	1	Reg Max Expires:	7200
Reg Retry Intvl:	30	Reg Retry Long Intvl:	1200
Reg Retry Random Delay:		Reg Retry Long Random Delay:	
Reg Retry Intvl Cap:			

Response Status Code Handling

SIT1 RSC:	SIT2 RSC:
SIT3 RSC:	SIT4 RSC:
Try Backup RSC:	Retry Reg RSC:

RTP Parameters

RTP Port Min:	16384	RTP Port Max:	16482
RTP Packet Size:	0.020	Max RTP ICMP Err:	0
RTCP Tx Interval:	0	No UDP Checksum:	no
Stats In BYE:	no		

SDP Payload Types

NSE Dynamic Payload:	100	AVT Dynamic Payload:	101
INFOREQ Dynamic Payload:		G726r16 Dynamic Payload:	98
G726r24 Dynamic Payload:	97	G726r32 Dynamic Payload:	2
G726r40 Dynamic Payload:	96	G729b Dynamic Payload:	99
EncapRTP Dynamic Payload:	112	RTP-Start-Loopback Dynamic Payload:	113
RTP-Start-Loopback Codec:	G711u	NSE Codec Name:	NSE
AVT Codec Name:	telephone-event	G711u Codec Name:	PCMU
G711a Codec Name:	PCMA	G726r16 Codec Name:	G726-16
G726r24 Codec Name:	G726-24	G726r32 Codec Name:	G726-32
G726r40 Codec Name:	G726-40	G729a Codec Name:	G729a
G729b Codec Name:	G729ab	G723 Codec Name:	G723

EncapRTP Codec Name: encaprtp

NAT Support Parameters

Handle VIA received:	no	Handle VIA rport:	no
Insert VIA received:	no	Insert VIA rport:	no
Substitute VIA Addr:	no	Send Resp To Src Port:	no
STUN Enable:	yes	STUN Test Enable:	yes
STUN Server:	stun2.3cx.com:3478	EXT IP:	
EXT RTP Port Min:		NAT Keep Alive Intvl:	15

Undo All Changes

Submit All Changes

[User Login](#) | [basic](#) | advanced

Copyright © 1992-2009 Cisco Systems, Inc. All Rights Reserved.