

# AAA Client Setup for mars01ba1

AAA Client IP Address

Shared Secret

Network Device Group

Authenticate Using

## RADIUS Key Wrap

Key Encryption Key

Message Authenticator Code Key

Key Input Format  ASCII  Hexadecimal

Log Update/Watchdog Packets from this AAA Client

## RADIUS Options

- Replace RADIUS Port info with Username from this AAA Client
- Log RADIUS Tunneling Packets from this AAA Client
- Match Framed-IP-Address with user IP address for accounting packets from this AAA Client

## TACACS+ Options

- Generate account stop packet for unexpected Single-Connect termination

### Single Connect Flag support

- Legacy TACACS+ Single Connect support for this AAA client
- TACACS+ Draft compliant Single Connect support for this AAA client

1. Enter the reporting IP (the IP address where events originated from) to ensure that the system processes the events.
2. \* denotes a required field.

Device Type: Edit host with security applications

<b>General</b>	<b>Reporting Applications</b>
----------------	-------------------------------

**Enter reporting application:**


→ **Device Name:** cis04ba1.topdanmark.local

→ **Select application:**

**Device Type**

Generic AAA Server

[mars01ba1] Device Discovery-Generic AAA Server - Microsoft Internet Explorer

 Nov 27, 2009 8:52:54 AM CET

Standalone: mars01ba1 v6.0

**AAA Server Configuration:**

Name:	<input type="text" value="cis04ba1"/>
Shared Secret:	<input type="password" value="...."/>
Re-enter Shared Secret:	<input type="password" value="...."/>
Authentication Port:	<input type="text" value="1812"/>
Accounting Port:	<input type="text" value="1813"/>

Copyright © 2003–2009 Cisco Systems, Inc.  
All rights reserved.



Nov 27, 2009 8:42:01 AM CET

Standalone: mars01ba1 v6.0

Login: [redacted] ::

**Connection to AAA server failed!**

Copyright © 2003–2009 Cisco Systems, Inc.  
All rights reserved.