

MIB Variables

Filter Source: All

Showing 6 records

<input type="checkbox"/>	Variable Name	OID
<input checked="" type="checkbox"/>	cpmCPUTotal5minRev	1.3.6.1.4.1.9.9.109.1.1.1.1.8
<input checked="" type="checkbox"/>	ciscoEnvMonTemperatureStatusValue	1.3.6.1.4.1.9.9.13.1.3.1.3
<input checked="" type="checkbox"/>	ciscoMemoryPoolFree	1.3.6.1.4.1.9.9.48.1.1.1.6
<input checked="" type="checkbox"/>	ciscoMemoryPoolUsed	1.3.6.1.4.1.9.9.48.1.1.1.5
<input checked="" type="checkbox"/>	Memory Utilization	N/A
<input checked="" type="checkbox"/>	sysUpTime	1.3.6.1.2.1.1.3

Date Range

Variable: ciscoEnvMonTemperatureStatusValue

Instance Name	Min(Celsius)	Max(Celsius)	Avg(Celsius)
CPU Die	39.00	43.00	40.98
NPE Inlet	20.00	23.00	21.57
NPE Outlet	21.00	24.00	22.33

Variable: ciscoMemoryPoolFree

Instance Name	Min(bytes)	Max(bytes)	Avg(bytes)
I/O	54871792.00	54905744.00	54895318.80
Processor	742110210.00	754484100.00	747654962.64

Variable: ciscoMemoryPoolUsed

Instance Name	Min(bytes)	Max(bytes)	Avg(bytes)
I/O	12203120.00	12237072.00	12213545.20
Processor	86305792.00	98679640.00	93135001.46

Variable: cpmCPUTotal5minRev

Instance Name	Min(%)	Max(%)	Avg(%)
Cisco 7200 Series Network Processing Engine NPE-G2	2.00	7.00	2.77

Variable: Memory Utilization

Instance Name	Min(%)	Max(%)	Avg(%)
I/O			0.00
Processor			0.00

Variable: sysUpTime

Instance Name	Min(csec)	Max(csec)	Avg(csec)
Device Availability	1.00	1.00	1.00
System Uptime			0.00