

Cisco Unified CM Administration
TII Cisco Unified Communications Solutions

Navigation: Cisco Unified CM Administration | administrator | About | Logout

System > Call Routing > Media Resources > Voice Mail > Device > Application > User Management > Bulk Administration > Help

Directory Number Configuration Related Links: [Configure Device \(SEP001562C27B7B\)](#)

Save | Delete | Reset | Add New

Status
Status: Ready

Directory Number Information

Directory Number* 2360
Route Partition PhonesPT
Description
Alerting Name Ans Skole
ASCII Alerting Name Ans Skole
 Allow Control of Device from CTI
Associated Devices SEP001562C27B7B
Edit Device | Edit Line Appearance
Dissociate Devices

Directory Number Settings

Voice Mail Profile < None > (Choose <None> to use system default)
Calling Search Space NationalCSS
Presence Group* Standard Presence group
User Hold MOH Audio Source < None >
Network Hold MOH Audio Source < None >
Auto Answer* Auto Answer Off

AAR Settings

AAR	Voice Mail	AAR Destination Mask	AAR Group
<input type="checkbox"/>	or		< None >

Retain this destination in the call forwarding history

Call Forward and Call Pickup Settings

	Voice Mail	Destination	Calling Search Space
Calling Search Space Activation Policy			Brug systemstandard
Forward All	<input type="checkbox"/> or		NationalCSS
Secondary Calling Search Space for Forward All			< None >
Forward Busy Internal	<input type="checkbox"/> or		InternCSS
Forward Busy External	<input type="checkbox"/> or		InternCSS
Forward No Answer Internal	<input type="checkbox"/> or		InternCSS
Forward No Answer External	<input type="checkbox"/> or		InternCSS
Forward No Coverage Internal	<input type="checkbox"/> or		InternCSS
Forward No Coverage External	<input type="checkbox"/> or		InternCSS
Forward on CTI Failure	<input type="checkbox"/> or		< None >
Forward Unregistered Internal	<input type="checkbox"/> or		InternCSS
Forward Unregistered External	<input type="checkbox"/> or		InternCSS
No Answer Ring Duration (seconds)			
Call Pickup Group		Ans Skole in InternPT	Find

MLPP Alternate Party Settings

Target (Destination)
MLPP Calling Search Space < None >
MLPP No Answer Ring Duration (seconds)

Line Settings for All Devices

Hold Reversion Ring Duration (seconds)
Hold Reversion Notification Interval (seconds)

Line 1 on Device SEP001562C27B7B

Display (Internal Caller ID) Ans Skole
may not see the proper identity of the caller.
Display text for a line appearance is intended for displaying text such as a name instead of a directory number for internal calls. If you specify a number, the person receiving a call

ASCII Display (Internal Caller ID) Ans Skole
Line Text Label
ASCII Line Text Label
External Phone Number Mask
Visual Message Waiting Indicator Policy* Use System Policy
Ring Setting (Phone Idle)* Brug systemstandard
Ring Setting (Phone Active) Brug systemstandard Applies to this line when any line on the phone has a call in progress.
Call Pickup Group Audio Alert Setting (Phone Idle) Brug systemstandard
Call Pickup Group Audio Alert Setting (Phone Active) Brug systemstandard
Monitoring Calling Search Space < None >

Multiple Call/Call Waiting Settings on Device SEP001562C27B7B

Note: The range to select the Max. Number of calls is: 1-200
Maximum Number of Calls* 4
Busy Trigger* 1 (Less than or equal to Max. Calls)

Forwarded Call Information Display on Device SEP001562C27B7B

Caller Name
 Caller Number
 Redirected Number
 Dialed Number

Users Associated with Line

Associate End Users

Save | Delete | Reset | Add New

* - indicates required item.
** - Changes to Line or Directory Number settings require restart.

Save Delete Reset Add New

Status
 Status: Ready

Directory Number Information

Directory Number* 2375
 Route Partition PhonesPT
 Description
 Alerting Name Ans skole, Centerklassen
 ASCII Alerting Name Ans skole, Centerklassen
 Allow Control of Device from CTI
 Associated Devices SEP001B54525320
 Dissociate Devices

Directory Number Settings

Voice Mail Profile < None > (Choose <None> to use system default)
 Calling Search Space NationalCSS
 Presence Group* Standard Presence group
 User Hold MOH Audio Source < None >
 Network Hold MOH Audio Source < None >
 Auto Answer* Auto Answer Off

AAR Settings

AAR or
 Retain this destination in the call forwarding history

Call Forward and Call Pickup Settings

	Voice Mail	Destination	Calling Search Space
Calling Search Space Activation Policy			Brug systemstandard
Forward All	<input type="checkbox"/> or <input type="checkbox"/>	<input type="text" value=""/>	NationalCSS
Secondary Calling Search Space for Forward All			< None >
Forward Busy Internal	<input checked="" type="checkbox"/> or <input type="checkbox"/>	2360	InternCSS
Forward Busy External	<input checked="" type="checkbox"/> or <input type="checkbox"/>	2360	InternCSS
Forward No Answer Internal	<input checked="" type="checkbox"/> or <input type="checkbox"/>	2360	InternCSS
Forward No Answer External	<input checked="" type="checkbox"/> or <input type="checkbox"/>	2360	InternCSS
Forward No Coverage Internal	<input type="checkbox"/> or <input type="checkbox"/>	<input type="text" value=""/>	InternCSS
Forward No Coverage External	<input type="checkbox"/> or <input type="checkbox"/>	<input type="text" value=""/>	InternCSS
Forward on CTI Failure	<input type="checkbox"/> or <input type="checkbox"/>	<input type="text" value=""/>	< None >
Forward Unregistered Internal	<input checked="" type="checkbox"/> or <input type="checkbox"/>	2360	InternCSS
Forward Unregistered External	<input checked="" type="checkbox"/> or <input type="checkbox"/>	2360	InternCSS
No Answer Ring Duration (seconds)	<input type="text" value=""/>		
Call Pickup Group	< None > <input type="button" value="Find"/>		

MLPP Alternate Party Settings

Target (Destination)
 MLPP Calling Search Space < None >
 MLPP No Answer Ring Duration (seconds)

Line Settings for All Devices

Hold Reversion Ring Duration (seconds) Setting the Hold Reversion Ring Duration to zero will disable the feature
 Hold Reversion Notification Interval (seconds) Setting the Hold Reversion Notification Interval to zero will disable the feature

Line 1 on Device SEP001B54525320

Display (Internal Caller ID) Ans skole, Centerklassen Display text for a line appearance is intended for displaying text such as a name instead of a directory number for internal calls. If you specify a number, the person receiving a call may not see the proper identity of the caller.
 ASCII Display (Internal Caller ID) Ans skole, Centerklassen
 Line Text Label
 ASCII Line Text Label
 External Phone Number Mask
 Visual Message Waiting Indicator Policy* Use System Policy
 Audible Message Waiting Indicator Policy* Standard
 Ring Setting (Phone Idle)* Brug systemstandard
 Ring Setting (Phone Active) Brug systemstandard Applies to this line when any line on the phone has a call in progress.
 Call Pickup Group Audio Alert Setting (Phone Idle) Brug systemstandard
 Call Pickup Group Audio Alert Setting (Phone Active) Brug systemstandard
 Recording Option* Opkaldsoptagelse er deaktiveret
 Recording Profile < None >
 Monitoring Calling Search Space < None >

Multiple Call/Call Waiting Settings on Device SEP001B54525320

Note: The range to select the Max Number of calls is: 1-200
 Maximum Number of Calls* 4
 Busy Trigger* 1 (Less than or equal to Max. Calls)

Forwarded Call Information Display on Device SEP001B54525320

Caller Name
 Caller Number
 Redirected Number
 Dialed Number

Users Associated with Line

Save Delete Reset Add New

i * - indicates required item.
i ** - Changes to Line or Directory Number settings require restart.

Subscriber Locator Screen - Microsoft Internet Explorer

Find and Select Subscriber

Find by:

Search all Cisco Unity servers

Matching Subscribers

Sort table by clicking column heading

No Matching Records Found

First Name	Last Name	Extension	Exchange Alias	Display name
------------	-----------	------------------	----------------	--------------

Subscriber Locator Screen - Microsoft Internet Explorer

Find and Select Subscriber

Find by:

Search all Cisco Unity servers

Matching Subscribers
Sort table by clicking column heading

No Matching Records Found

First Name	Last Name	Extension	Exchange Alias	Display name
------------	-----------	-----------	----------------	--------------