

Cisco Unified CM Administration

Navigation: Cisco Unified CM Administration | Start | administrator | About | Logout

Related Links: Back To Find/List

Directory Number Configuration

Status
Status: Ready

Directory Number Information

Directory Number*	1011
Route Partition	PhonesPT
Description	
Alerting Name	Karen Kjems Lyngvad
ASCII Alerting Name	Karen Kjems Lyngvad
<input checked="" type="checkbox"/> Allow Control of Device from CTI	
Associated Devices	udp_1011

Edit Device **Edit Line Appearance**

Dissociate Devices

Directory Number Settings

Voice Mail Profile	< None >	(Choose <None> to use system default)
Calling Search Space	NationalCSS	
Presence Group*	Standard Presence group	
User Hold MOH Audio Source	< None >	
Network Hold MOH Audio Source	< None >	

AAR Settings

AAR	<input checked="" type="checkbox"/> or	AAR Destination Mask	AAR Group
			< None >
<input type="checkbox"/> Retain this destination in the call forwarding history			

Call Forward and Call Pickup Settings

Voice Mail	Destination	Calling Search Space	
Forward All	1000	Brug systemstandard	
Secondary Calling Search Space for Forward All		InternCSS	
Forward Busy Internal		< None >	
Forward Busy External		InternCSS	
Forward No Answer Internal		InternCSS	
Forward No Answer External		InternCSS	
Forward No Coverage Internal		InternCSS	
Forward No Coverage External		InternCSS	
Forward on CTI Failure		< None >	
Forward Unregistered Internal		InternCSS	
Forward Unregistered External		InternCSS	
No Answer Ring Duration (seconds)			
Call Pickup Group	Borgerservice1 in InternPT	<input type="button" value="Find"/>	

MLPP Alternate Party Settings

Target (Destination)	
MLPP Calling Search Space	< None >
MLPP No Answer Ring Duration (seconds)	

Line Settings for All Devices

Hold Reversion Ring Duration (seconds)		Setting the Hold Reversion Ring Duration to zero will disable the feature
Hold Reversion Notification Interval (seconds)		Setting the Hold Reversion Notification Interval to zero will disable the feature

Buttons:

Notes:
*. indicates required item.
**. Changes to Line or Directory Number settings require restart.

Directory number 1011 configuration.

Cisco Unified CM Administration

Navigation: Cisco Unified CM Administration | Start | administrator | About | Logout

Related Links: Back To Find/List

Directory Number Configuration

Status
Status: Ready

Directory Number Information

Directory Number*	1595
Route Partition	PhonesPT
Description	
Alerting Name	Carl-Marius Steensen
ASCII Alerting Name	Carl-Marius Steensen
<input checked="" type="checkbox"/> Allow Control of Device from CTI	
Associated Devices	SEP0014691B5534 SEP0013C4ECA124 SEP0013C4FB80E
Edit Device Edit Line Appearance	
Dissociate Devices	<input type="button" value="▼"/>

Directory Number Settings

Voice Mail Profile	< None >	(Choose <None> to use system default)
Calling Search Space	NationalCSS	
Presence Group*	Standard Presence group	
User Hold MOH Audio Source	< None >	
Network Hold MOH Audio Source	< None >	

AAR Settings

AAR	Voice Mail	AAR Destination Mask	AAR Group
<input type="checkbox"/> or			< None >
<input type="checkbox"/> Retain this destination in the call forwarding history			

Call Forward and Call Pickup Settings

	Voice Mail	Destination	Calling Search Space
Calling Search Space Activation Policy			Brug systemstandard
Forward All	<input type="checkbox"/> or		InternCSS
Secondary Calling Search Space for Forward All			< None >
Forward Busy Internal	<input type="checkbox"/> or		InternCSS
Forward Busy External	<input type="checkbox"/> or		InternCSS
Forward No Answer Internal	<input type="checkbox"/> or		InternCSS
Forward No Answer External	<input type="checkbox"/> or		InternCSS
Forward No Coverage Internal	<input type="checkbox"/> or		InternCSS
Forward No Coverage External	<input type="checkbox"/> or		InternCSS
Forward on CTI Failure	<input type="checkbox"/> or		< None >
Forward Unregistered Internal	<input type="checkbox"/> or		InternCSS
Forward Unregistered External	<input type="checkbox"/> or		InternCSS
No Answer Ring Duration (seconds)			
Call Pickup Group	IT-Applikationer in InternPT	<input type="button" value="Find"/>	

MLPP Alternate Party Settings

Target (Destination)	
MLPP Calling Search Space	< None >
MLPP No Answer Ring Duration (seconds)	

Line Settings for All Devices

Hold Reversion Ring Duration (seconds)	0	Setting the Hold Reversion Ring Duration to zero will disable the feature
Hold Reversion Notification Interval (seconds)	0	Setting the Hold Reversion Notification Interval to zero will disable the feature

Action Buttons: [Save](#) [Delete](#) [Copy](#) [Reset](#) [Add New](#)

Notes:

- * - indicates required item.
- ** - Changes to Line or Directory Number settings require restart.

Directory number 1595 configuration.

Cisco Unified CM Administration

Navigation: Cisco Unified CM Administration | Status | administrator | About | Logout

Related Links: Back to Find List Users

End User Configuration

Status
Status: Ready

User Information

User ID*	dr16167	<input type="button" value="Edit Credential"/>
Password	*****	<input type="button" value="Edit Credential"/>
Confirm Password	*****	<input type="button" value="Edit Credential"/>
PIN	*****	<input type="button" value="Edit Credential"/>
Confirm PIN	*****	<input type="button" value="Edit Credential"/>
Last name*	Lyngvad	
Middle name	Kjems	
First name	Karen	
Telephone Number	1011	
Mail ID	dr16167	
Manager User ID		
Department	BorgerService	
User Locale	< None >	
Associated PC		
Digest Credentials	*****	
Confirm Digest Credentials	*****	
Name Dialing	LyngvadKjemsKaren	
Number of Digits needed for the Unique AA Name	8	

Device Associations

Controlled Devices: SEP001795180977, SEP001795180E32, SEP00179551FE9B, SEP0019E74470SE, SEP0019E74464C1

Extension Mobility

Available Profiles: NO, logout 7941, logout 7960, tester, testers

Controlled Profiles:

Default Profile: -- Not Selected --

Presence Group*: Standard Presence group

SUBSCRIBE Calling Search Space: < None >

Allow Control of Device from CTI

Directory Number Associations

Primary Extension: 1011 in PhoneSPT

IPCC Extension: < None >

Mobility Information

Enable Mobility
 Primary User Device: < None >

Enable Mobile Voice Access
 Maximum Wait Time for Desk Pickup*: 10000
 Remote Destination Limit*: 4
 Remote Destination Profiles: [View Details](#)

CAPF Information

Associated CAPF Profiles: [View Details](#)

Permissions Information

Groups: Standard CCM End Users, Standard CTI Enabled

[View Details](#)

Roles: Standard CCM End Users, Standard CCMUSER Administration, Standard CTI Enabled

i * - indicates required item.

End-user dr16167 configuration.

Cisco Unified CM Administration

Navigation: Cisco Unified CM Administration | Start | administrator | About | Logout

Related Links: Back to Find List Users

End User Configuration

Status
(i) Status: Ready

User Information

User ID*	dr18147	<input type="button" value="Edit Credential"/>
Password	*****	<input type="button" value="Edit Credential"/>
Confirm Password	*****	
PIN	*****	<input type="button" value="Edit Credential"/>
Confirm PIN	*****	
Last name*	Steenesen	
Middle name		
First name	Carl-Marius	
Telephone Number	1595	
Mail ID	boms	
Manager User ID		
Department	IT	
User Locale	< None >	
Associated PC		
Digest Credentials	*****	
Confirm Digest Credentials	*****	
Name Dialing	SteenesenCarl-Marius	
Number of Digits needed for the Unique AA Name	9	

Device Associations

Controlled Devices: SEP001469185534

Extension Mobility

Available Profiles
 NO
 logout 7941
 logout 7960
 tester
 testers

Controlled Profiles

Default Profile: -- Not Selected --

Presence Group*: Standard Presence group

SUBSCRIBE Calling Search Space: < None >

Allow Control of Device from CTI

Directory Number Associations

Primary Extension: 1595 in PhonesPT

IPCC Extension: 1595 in PhonesPT

Mobility Information

Enable Mobility
 Primary User Device: < None >

Enable Mobile Voice Access
 Maximum Wait Time for Desk Pickup*: 10000

Remote Destination Limit*: 4

Remote Destination Profiles

[View Details](#)

CAPF Information

Associated CAPF Profiles

[View Details](#)

Permissions Information

Groups (Admin
 IT-Applikationsgruppe administrator
 Standard CCM End Users
 Standard CTI Enabled
 Standard RealtimeAndTraceCollection)

[View Details](#)

Roles (AdminFU
 Standard CCM Admin Users
 Standard CCM End Users
 Standard CCMUSER Administration
 Standard CTI Enabled)

(i) *- indicates required item.

End-user dr18147 configuration.