



config_to-send.txt

```
interface FastEthernet0
description $ES_WAN$$ETH-WAN$$FW_OUTSIDE$
ip address 66.66.66.1 255.255.255.248
ip mask-reply
no ip unreachables
no ip proxy-arp
ip nat outside
ip virtual-reassembly
ip route-cache flow
speed 10
full-duplex
interface BVI1
description $ES_LAN$$FW_INSIDE$
ip address 192.168.0.50 255.255.255.0
ip access-group 103 in
ip access-group 103 out
ip helper-address 192.168.0.2
ip nat inside
ip virtual-reassembly
interface Vlan1
  no ip address
  ip tcp adjust-mss 1452
  bridge-group 1
ip route 0.0.0.0 0.0.0.0 66.66.66.5

ip http server
ip http port 8000
ip http access-class 14
no ip http secure-server
ip http timeout-policy idle 60 life 86400 requests 10000
ip nat inside source list 1 interface FastEthernet0 overload
ip nat inside source static tcp 192.168.0.50 23 66.66.66.1 23 extendable
ip nat inside source static tcp 192.168.0.1 389 66.66.66.1 389 extendable
ip nat inside source static tcp 192.168.0.1 21 66.66.66.4 21 extendable
ip nat inside source static udp 192.168.0.1 53 66.66.66.1 53 extendable
ip nat inside source static tcp 192.168.0.1 990 66.66.66.1 990 extendable
ip nat inside source static tcp 192.168.0.2 25 66.66.66.1 25 extendable
ip nat inside source static tcp 192.168.0.2 110 66.66.66.1 110 extendable
ip nat inside source static tcp 192.168.0.2 143 66.66.66.1 143 extendable
ip nat inside source static tcp 192.168.0.2 443 66.66.66.1 443 extendable
ip nat inside source static tcp 192.168.0.2 2525 66.66.66.1 2525 extendable
ip nat inside source static tcp 192.168.0.3 54 66.66.66.1 54 extendable
ip nat inside source static tcp 192.168.0.3 80 66.66.66.1 80 extendable
ip nat inside source static tcp 192.168.0.3 8080 66.66.66.1 8080 extendable
ip nat inside source static tcp 192.168.0.3 54 66.66.66.3 54 extendable
ip nat inside source static tcp 192.168.0.4 3306 66.66.66.1 3306 extendable
ip nat inside source static tcp 192.168.0.4 3306 68.68.68.2 3306 extendable
ip nat inside source static 192.168.0.2 66.66.66.2
ip nat inside source static 192.168.0.1 66.66.66.4
ip nat inside source static 192.168.0.4 68.68.68.3
```