

run-config1.txt  
(Cisco Controller) >show run-config

Press Enter to continue...

System Inventory  
Burned-in MAC Address..... 00:1B:D5  
Crypto Accelerator 1..... Absent  
Crypto Accelerator 2..... Absent  
Power Supply 1..... Absent  
Power Supply 2..... Present, OK

Press Enter to continue Or <Ctl Z> to abort

System Information  
Manufacturer's Name..... Cisco Systems Inc.  
Product Name..... Cisco Controller  
Product Version..... 4.0.217.0  
RTOS Version..... 4.0.217.0  
Bootloader Version..... 4.0.217.0  
Build Type..... DATA + WPS  
  
System Name..... wlrc01  
System Location.....  
System Contact.....  
System ObjectID.....  
IP Address..... 192.168.1.3  
System Up Time..... 3 days 21 hrs 55 mins 22 secs  
  
Configured Country..... United States  
Operating Environment..... Commercial (0 to 40 C)  
Internal Temp Alarm Limits..... 0 to 65 C  
Internal Temperature..... +31 C

State of 802.11b Network..... Enabled  
State of 802.11a Network..... Enabled  
Number of WLANS..... 1  
3rd Party Access Point Support..... Disabled  
Number of Active Clients..... 0

Burned-in MAC Address..... 00:1B:D5  
Crypto Accelerator 1..... Absent  
Crypto Accelerator 2..... Absent  
Power Supply 1..... Absent  
Power Supply 2..... Present, OK

Press Enter to continue Or <Ctl Z> to abort

Switch Configuration  
802.3x Flow Control Mode..... Disable  
Current LWAPP Transport Mode..... Layer 3  
LWAPP Transport Mode after next switch reboot.... Layer 3  
FIPS prerequisite features..... Disabled

Press Enter to continue Or <Ctl Z> to abort

Network Information  
RF-Network Name..... MobilityGroupName  
Web Mode..... Disable  
Secure Web Mode..... Enable  
Secure Shell (ssh)..... Enable  
Telnet..... Disable  
Ethernet Multicast Mode..... Disable Mode: Ucast  
Ethernet Broadcast..... Disable

run-config1.txt

User Idle Timeout..... 300 seconds  
ARP Idle Timeout..... 300 seconds  
ARP Unicast Mode..... Disabled  
Cisco AP Default Master..... Disable  
Mgmt Via Wireless Interface..... Disable  
Mgmt Via Dynamic Interface..... Disable  
Bridge AP Zero Config..... Enable  
Bridge Shared Secret.....  
Allow Old Bridging Aps To Authenticate..... Disable  
Over The Air Provisioning of AP's..... Enable  
Mobile Peer to Peer Blocking..... Disable  
Apple Talk ..... Disable  
AP Fallback ..... Enable  
Web Auth Redirect Ports ..... 80  
Fast SSID Change ..... Disabled  
802.3 Bridging ..... Disable

Press Enter to continue Or <Ctl Z> to abort

Port Summary

Pr	Type	STP Stat	Admin Mode	Physical Mode	Physical Status	Link Status	Link Trap	Mcast Appliance	POE
1	Normal	Forw	Enable	Auto	1000 Full	Up	Enable	Enable	N/A
2	Normal	Disa	Enable	Auto	1000 Full	Down	Enable	Enable	N/A

Press Enter to continue Or <Ctl Z> to abort

AP Summary

AP Name Port	Slots	AP Model	Ethernet MAC	Location
ITS 1	2	AIR-LAP1231G-A-K9	00:1b:d5	Ground Floo
Library1 1	2	AIR-AP1231G-A-K9	00:14:a8	Library1
Library4 1	2	AIR-AP1231G-A-K9	00:14:a8	Library4

Press Enter to continue Or <Ctl Z> to abort