



Cisco Aironet 1200 Series Access Point



- HOME
- EXPRESS SET-UP
- EXPRESS SECURITY
- NETWORK MAP
- ASSOCIATION
- NETWORK INTERFACES
- SECURITY**
- Admin Access
- Encryption Manager
- SSID Manager**
- Server Manager
- Local RADIUS Server
- Advanced Security
- SERVICES
- WIRELESS SERVICES
- SYSTEM SOFTWARE
- EVENT LOG

Hostname AP1

AP1 uptime is 18 hours, 8 minutes

+ Security: Global SSID Manager

+ SSID Properties

+ Current SSID List

< NEW >

AP1

SSID: AP1

VLAN: < NONE > [Define VLANs](#)

Backup 1:

Backup 2:

Backup 3:

Interface: ☐ Radio0-802.11G☒ Radio1-802.11A

Network ID: (0-4096)

[Delete](#)

Client Authentication Settings

Methods Accepted:



Open

Authentication:

< NO ADDITION >



Shared

Authentication:

< NO ADDITION >



Network EAP:

< NO ADDITION >

Server Priorities:

EAP Authentication Servers

Use Defaults [Define Defaults](#)

Customize

Priority 1: < NONE >

Priority 2: < NONE >

Priority 3: < NONE >

MAC Authentication Servers

Use Defaults [Define Defaults](#)

Customize

Priority 1: < NONE >

Priority 2: < NONE >

Priority 3: < NONE >

Client Authenticated Key Management

Key Management:

< NONE >

☐ CCKM☐ WPA

WPA Pre-shared Key:

☒ ASCII ☐ Hexadecimal**Accounting Settings**☐ Enable Accounting**Accounting Server Priorities:**☒ Use Defaults [Define Defaults](#)☐ CustomizePriority 1: Priority 2: Priority 3: **General Settings**☒ Advertise Extended Capabilites of this SSID☐ Advertise Wireless Provisioning Services (WPS) Support☒ Advertise this SSID as a Secondary Broadcast SSID☐ Enable IP Redirection on this SSIDIP Address: IP Filter (optional): [Define Filter](#)Association Limit
(optional): (1-255)Call Admission Control: ☐ Enable ☒ Disable**EAP Client (optional):**


Username:

Password:


Multiple BSSID Beacon Settings**Multiple BSSID Beacon**☐ Set SSID as Guest Mode☐ Set Data Beacon Rate (DTIM): (1-100)**Guest Mode/Infrastructure SSID Settings**

Radio0-802.11G:


Set Beacon Mode:

☒ Single BSSIDSet Single Guest Mode SSID: < NONE > ☐ Multiple BSSID



Set Infrastructure SSID:

< NONE > ☐ Force Infrastructure Devices to associate only to this SSID**Radio1-802.11A:**

Set Beacon Mode:

☒ Single BSSIDSet Single Guest Mode SSID: < NONE > ☐ Multiple BSSID

Set Infrastructure SSID:

< NONE > ☐ Force Infrastructure Devices to associate only to this SSID

Copyright (c) 1992-2007 by Cisco Systems, Inc.